



TRACTION

EX™




- 1. EX™ - CTL
- 2. Normal
- 3. 22 and 26 mm
- 4. Narrow and Standard
- 5. SYM
- 6. NC, SC and DC

774-960 mm width




OF™




- 1. OF™ - CTL
- 2. Normal
- 3. 22 and 26 mm
- 4. Narrow, Standard and Soft
- 5. SYM
- 6. NC, SC and DC

655-906 mm width




EVO™



- 1. EVO™ - CTL
- 2. Light and Normal
- 3. 22 and 26 mm
- 4. Narrow, Standard and Soft
- 5. SYM
- 6. NC, SC and DC

695-960 mm width



ALL-ROUND

ECO™



- 1. ECO™ - CTL
- 2. Normal
- 3. 22 and 26 mm
- 4. Narrow, Standard and Soft
- 5. SYM
- 6. NC, SC and DC

615-944 mm width



KovaX™



- 1. KovaX™ - CTL
- 2. Normal and Plus
- 3. 22 and 26 mm
- 4. Narrow, Standard and Soft
- 5. SYM and OSS
- 6. NC, SC and DC

680-950 mm width




Baltic™



- 1. Baltic™ - CTL
- 2. Light and Normal
- 3. 22 and 26 mm
- 4. Narrow, Standard and Soft
- 5. SYM, ASYM and OSS
- 6. NC, SC, DC and RC

650-1210 mm width



CoverB™



- 1. CoverB™ - CTL
- 2. Light and Normal
- 3. 22 and 26 mm
- 4. Narrow, Standard and Soft
- 5. SYM, ASYM and OSS
- 6. NC, SC, DC and RC

670-1220 mm width



FLOTATION

Skidder Wheel Tracks™

